



Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-3G HHD 230V 1N 50Hz

19089570

04/05/2022

DENOMINATION:

Refrigerated counter with drawers - Concept 700 Gastronorm with 3 doors (2H+1D).

DESCRIPTION :

- Structure built with AISI-304 stainless steel
 - 50 mm, 40 kg/m3 injected polyurethane insulation.
 - Forced draught cooling system inside the room.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.
 - Easier loading and unloading thanks to its door self-closing and stay open features.
 - Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).
 - Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Interior LED lighting (only for models with glass doors).
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - 10 cm high splashback.
 - Working temperature: from 0 °C to +8 °C (refrigerators) and from -18 °C to -22 °C (freezers).
 - Tested in climatic class IV.
- Refrigerated counters with "H" drawers.
VERSATILITY: Different sets of drawers for the most specific requirements.
ROBUSTNESS: Our perforated stainless steel drawers can stand loads up to 40 kg.

POSSIBLE OPTIONS :

- Stainless Backing
- Wheels Kit (Factory Assembly)
- British plug
- Door frame resistance
- Granite worktop
- Left group
- Without breastplate
- Without Countertop


POSSIBLE ACCESSORIES :

- REFRIGERATION
- ACCESSORIES
- ACCESSORIES FOR REFRIGERATION
- GASTRONORM GRIDS

SUPPLIED ACCESSORIES:

- 12035781 GN 1/1 grid in epoxy (530x325) 1
- 12037936 Guide for grill GN-1/1 - wall - 562 mm - 1 piece 4

DIMENSIONS



X Width	1792 mm	X Gross width	1910 mm
Y Depth	700 mm	Y Gross depth	825 mm
Z Height	850 mm	Z Gross height	1000 mm
Net Weight	155,0 kg	Gross Weight	163,0 kg
Net volume	1,066 m3	Gross volume	1,576 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,203 kW
Amperage (A)	0,96 A
Voltage	230V - 1N
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,361 kW
Annual elec. consumption	931,00 kWh
Power consumption 24h	2,55 kWh
Gross internal volume	428 L
Refrigeration net.vol	184 L
Climate class	4
Cooling gas load	64,000 g
Clasif. Energy efficiency	C
Energy Efficiency Index	41,18 %
Model Type	Counter Cabinet

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1+T-2A
--------------------------	----------

OTHERS

Number of doors	1
Condensation system	Vent.





Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
CCP-3G HHD 230V 1N 50Hz

19089570

04/05/2022

