

# ALP01S

SOFT-TOUCH PROGRAMMABLE WARE WASHERS - RACK 600 x 700 mm



## PRODUCT DESCRIPTION

Stainless steel structure 18/10 AISI 304. Double-skinned balanced dual door. Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Washing system having 3 wash arms in the upper part and 4 wash arms in the lower part with particularly shaped jets for keeping them free from solid waste.

**Three working cycles:** 120 seconds, 240 seconds or continuous.

High capacity **double-boiler system**.

**Double stainless steel surface filters** in the tank for collecting solid waste.

Low tension (24V) **soft-touch** control panel. Temperature thermometer.

Possibility to change the cycle parameters thanks to palmtop with simple logic. Possibility to program the working cycle.

The programmable **THERMOLOCK** system ensures that the rinsing cycle starts only at the temperature of 85°C: the ideal temperature for strongly reducing the bacterial load.

Steam is carried out through a chimney.

The built-in **W.A.G.P.** system ensures excellent rinsing and prevents dirty water from flowing back to the main water system.

Rack: 600 x 700 mm. Possibility to wash baking trays and other items **up to 800 mm**.

The lower wash pump is more powerful than the upper wash pump and it has a delayed action, so that items to be washed do not move from their position when the washing cycle starts.

**Standard equipped** with built-in rinse aid dispenser for the best drying results. **Standard equipped** with built-in connection for detergent dispenser.

Wide range of options available **on demand**. Winding shower available **on demand**.

**Standard equipped** with a stainless steel plain basket, a rack for baking trays and a ladles rack.



## TECHNICAL SPECIFICATIONS

**Width:** 800 mm  
**Depth:** 860 mm  
**Height:** 2090 mm  
**Volume:** 1.44 m<sup>3</sup>  
**Rack dimensions:** 600x700 mm  
**Useful height:** 850  
**Working cycles:** 120-240 + inf. sec  
**Electrical power:** 12.70 kW  
**Electric power:** 230 V / 3 - 400 V / 3+N/ 50-60 Hz  
**Racks/Hour:** 30-15  
**WAGP:** Standard

